

Configurer Autodiscover et Autoconfig



DNS

```
_autodiscover._tcp.yourdomain.com. 3600 IN SRV 10 10 443 mail.yourmx.com.
```

Autodiscover pour Outlook

[autodiscover.php](#)

```
<?php
$postData = file_get_contents('php://input'); //Autodiscover requests
are HTTP posts with XML content
$xml = simplexml_load_string($postData);
$user = $xml->Request->EmailAddress; //copy the email address from the
request into a variable

//set Content-Type
header("Content-Type: application/xml");
?>
<?php echo '<?xml version="1.0" encoding="utf-8" ?>'; ?>
<Autodiscover
xmlns="http://schemas.microsoft.com/exchange/autodiscover/responseschem
a/2006">
<Response
xmlns="http://schemas.microsoft.com/exchange/autodiscover/outlook/respo
nseschema/2006a">
<Account>
<AccountType>email</AccountType>
<Action>settings</Action>
<Protocol>
<Type>POP3</Type>
<Server>mail.yourmx.com</Server>
<Port>995</Port>
<LoginName><?php echo $user; ?></LoginName>
<DomainRequired>off</DomainRequired>
<SPA>off</SPA>
<SSL>on</SSL>
<AuthRequired>on</AuthRequired>
<DomainRequired>on</DomainRequired>
```

```
</Protocol>
<Protocol>
<Type>IMAP</Type>
<Server>mail.yourmx.com</Server>
<Port>993</Port>
<DomainRequired>on</DomainRequired>
<LoginName><?php echo $user; ?></LoginName>
<SPA>off</SPA>
<SSL>on</SSL>
<Encryption>Auto</Encryption>
<AuthRequired>on</AuthRequired>
</Protocol>
<Protocol>
<Type>SMTP</Type>
<Server>mail.yourmx.com</Server>
<Port>587</Port>
<DomainRequired>on</DomainRequired>
<LoginName><?php echo $user; ?></LoginName>
<SPA>off</SPA>
<Encryption>Auto</Encryption> <!-- if your server requires encryption
other than SSL -->
<AuthRequired>on</AuthRequired>
<UsePOPAuth>on</UsePOPAuth>
<SMTPLast>off</SMTPLast>
</Protocol>
</Account>
</Response>
</Autodiscover>
```

Directives Apache

```
ServerAlias autoconfig.*
RewriteEngine On
RewriteCond %{HTTPS} !on [OR]
RewriteCond %{HTTP_HOST} !^discover\.my-service\.com$
RewriteRule ^(.*)$ https://discover.my-service.com$1 [R=301]
```

Certificat SSL

Remember to get a SIGNED SSL Cert.

Autoconfig pour Thunderbird

config-v1.1.xml

```
<?xml version="1.0" encoding="UTF-8"?>

<clientConfig version="1.1">
  <emailProvider id="domain.tld">
    <domain>domain.tld</domain>
    <displayName>Mail</displayName>
    <displayShortName>Mail</displayShortName>
    <incomingServer type="pop3">
      <hostname>mailserver.domain.tld</hostname>
      <port>995</port>
      <socketType>SSL</socketType>
      <authentication>password-cleartext</authentication>
      <username>%EMAILADDRESS%</username>
      <pop3>
        <leaveMessagesOnServer>true</leaveMessagesOnServer>
        <downloadOnBiff>true</downloadOnBiff>
      </pop3>
    </incomingServer>
    <incomingServer type="imap">
      <hostname>mailserver.domain.tld</hostname>
      <port>993</port>
      <socketType>SSL</socketType>
      <authentication>password-cleartext</authentication>
      <username>%EMAILADDRESS%</username>
    </incomingServer>
    <outgoingServer type="smtp">
      <hostname>mailserver.domain.tld</hostname>
      <port>587</port>
      <socketType>STARTTLS</socketType>
      <authentication>password-cleartext</authentication>
      <username>%EMAILADDRESS%</username>
    </outgoingServer>
  </emailProvider>
</clientConfig>
```

From:
<https://www.abonnel.fr/> - notes informatique & technologie

Permanent link:
<https://www.abonnel.fr/informatique/serveur/web-linux-apache/configurer-autodiscover>

Last update: 2023/02/09 17:12

